

Index

SYMBOLS

`&&` (and), 38, 41, 45
`*` (asterisk)
 for multiplication, 25, 28
 as splat mark, 123, 131
`@` (at sign), 143
 for instance variables, 150
`@@`, for class variables, 148
`@name=`, 142
`\n` (newline), 268, 272
`:` (colon)
 for hash, 76
 for symbol, 94
`::`, scope resolution operator,
 221, 231
`,` (comma), for separating
 key-value pairs, 75
`{}` (curly brackets), for
 do/end, 57, 62
`$` (dollar sign), 10, 316
 for global variables, 147
`$home` variable, 169
`..` (dots), in ranges, 80, 89
`./`, for file location,
 219–220, 230
`...?`, for finishing your
 thought in IRB, 318
`=` (equal sign), 22–23
 for default parameters,
 119
 in method name, 159
`==` (equal to), 41
`=>` (hash rockets), 76
 for IRB response, 15
 for symbol, 96
`!` (not), 39, 41, 45
`!=` (not equal to), 41
`>` (greater than), 40
`>=` (greater than or
 equal to), 40
`>>`, and IRB prompt, 15

`#{}`, for inserting variable
 value into string,
 35, 45
`<` (less than), 40
 for calling subclass, 188
 for inheritance, 185
`<<` (shovel operator), 84
`<=` (less than or equal to), 40
`()` (parentheses), 115, 119
`?` (question mark)
 and colon, as if/else
 alternative, 241
 methods with, 260
`""` (quotation marks), 11, 26
 for strings, 22
`;` (semicolon), to end line of
 code, 212
`[]` (square brackets)
 for arrays, 54, 86
 for hash values, 87
`|` (vertical pipe), in do/end, 57
`||` (or), 41, 45
`||=`, 237–238
`_` (underscore), 23
 in symbol names, 94

A

`'a'` (add) mode, 271, 281
`'a+'` (add and read)
 mode, 272
Account class, 199–203
 instance variables, 201
addition, 25
analyze method, 225–226
and (`&&`), 38, 41, 45
another_minstrel.rb file, 158
another_minstrel_2.rb file,
 159–160
another_minstrel_3.rb
 file, 161
ArgumentError error, 118

arguments
 for methods, 117–120
 vs. parameters, 118
array literal syntax, 67
arrays, 54–58, 61
 within arrays, 66–68
 contents, 67
 creating, 67, 85
 first method, 68
 iterating through, 72–74
 methods for, 85
 moving to next item, 55
 sample method, 84
 for storing names, 278
asterisk (`*`)
 for multiplication, 25, 28
 as splat mark, 123, 131
at sign (`@`), 143
 for instance variables, 150
`attr_accessor`, 160, 161, 166,
 174, 182, 183–184,
 194, 303
`attr_reader`, 160, 161, 162,
 173, 174, 197, 303
`attr_writer`, 160, 173, 303

B

backward strings, 27–28
ballad.rb file, 165
beginning of file, going
 to, 272
blank line, removing from
 input, 44
block methods, 124–127
`block_given` method, 126
blocks of code, 57, 62, 73
 defining variable
 within, 145
 for methods, 132
 opening file with, 269, 280
 pipe character (`|`) in, 78

- blocks of code, *continued*
 - and splat parameters, 125
 - variable inside, 171
 - variable scope and, 146
 - Booleans, 32, 45, 261
 - and simplifying code, 244
 - break if statement, 59
 - built-in Ruby objects, ID numbers, 137
- C**
- calling a method, 23–24
 - case statement, 242–243, 257, 260
 - cd command, 13, 316
 - characters, 29
 - child class, 188, 204
 - chomp method, 44
 - class keyword, 141, 188, 203
 - class methods, 155
 - class << self syntax, 156–157
 - class variables, 143, 148–149, 165, 170
 - classes, 67, 182–188
 - adding methods, 156–157
 - creating, 140–143, 165
 - defining, 182
 - defining local variable outside, 152–153
 - in different files, 230
 - extending module into, 214
 - local variables inside definition, 145
 - methods for, 153
 - and objects, 137–140, 167–170
 - subclass and superclass, 188–193
 - clear the screen, in IRB, 318
 - close method, 270, 280
 - cmd.exe, 6
 - code
 - de-duplicating, 249–255
 - downloading gems, 220
 - DRY (Don't Repeat Yourself) code, 185–188
 - indentation, 39
 - preloaded, 223
 - refactoring, 231
 - reusing, 303
 - running one line at a time, 14
 - semicolon (;) to end line, 212
 - writing and running, 8
 - writing to file, 27
 - Code School, 307
 - Codecademy, 307
 - colon (:)
 - for hash, 76
 - for symbol, 94 - colons (::), scope resolution operator, 221, 231
 - colorize.rb file, 211, 224
 - combining, methods, vs. size management, 251–254
 - comma (,), for separating key-value pairs, 75
 - command line, 5
 - command not found error, 316
 - command prompt, in Windows, 6
 - commands
 - following object and dot, 24
 - typing, 16
 - compiling, 10
 - Computing Contraption, 16
 - conditional assignment
 - of value to variable, 238
 - conditional values, ||= for setting, 258–259
 - conditionals, 38, 240–242
 - constants, 213–214, 227
 - looking up, 221–224
 - control flow, 38, 45, 302
 - CTRL-C, for stopping IRB, 290, 318
 - curly brackets ({}), for do/end, 57, 62
- D**
- datatypes, 67
 - debugging, 309–310
 - de-duplicating code, 249–255
 - def keyword, 114, 124, 130, 303
 - default parameters, 119, 130
 - default value, for variables, 237
 - delete method, 99, 103
 - for keys from hashes, 107
 - directories, 34. *See also* folders
 - division, 25
 - do block, 83
 - do/end syntax, 57, 62
 - Dog class, 184
 - dollar sign (\$), 10, 316
 - for global variables, 147
 - Don't Repeat Yourself (DRY) code, 185–188
 - dots (.), in ranges, 80, 89
 - downloading
 - gems, 220
 - Ruby, 4
 - DRY (Don't Repeat Yourself) code, 185–188
- E**
- each do, 59, 78, 83
 - each method, 57, 61–62, 83, 308
 - echo, 27
 - element in array, 55
 - else statement, 38, 39, 45
 - with unless, 239
 - elsif statement, 38–39, 45
 - empty? method, 69, 85, 88
 - for hash, 77

- end keyword
 - for class definition, 141
 - for if statement, 38
 - for methods, 114, 130
 - for while loop, 52
- Enumerable module, 308
- equal sign (=), 22–23
 - for default parameters, 119
 - in method name, 159
- Errno:: ENOENT: No such file or directory error, 275
- errors, 315–319
 - ArgumentError, 118
 - avoiding while working with files, 275–277
 - Errno:: ENOENT: No such file or directory, 275
 - IOError, 211
 - NameError, 146, 171, 221, 317
 - NoMethodError, 155, 159, 162, 212, 228
 - NoMethodError: undefined method, 24
 - 'ruby' is not recognized ... error message, 6
 - SyntaxError, 96
 - TypeError, 317–318
 - when running Ruby scripts, 315–316
 - using IRB, 316–319
 - in variables, 145–147
- even? method, 252
- exceptions, handling, 309
- .exe file, running, 7
- exist? method, 275, 283
- exit, from IRB, 11
- extend statement, 214, 227, 303

F

- false, 32, 45, 262
- falsey values, 246, 247, 262
- file.close method, 280

- File.exist? method, 275
- File.open method, 268–269, 280
- file.read method, 280
- file.rewind method, 272, 274, 282
- files
 - ./ for location, 219–220
 - adding and writing to, 270–274
 - avoiding errors while working with, 275–277
 - close method, 270
 - opening, 267, 268–270
 - pulling Ruby code from, 218
 - working with, 280
 - writing code as, 27
- find_person method, 134
- finishing your thought (...?), in IRB, 318
- first method, 85
 - for arrays, 68, 71, 80
 - for range, 89
- first_try.rb file, 255–256
- flow.rb file, 34
- flying_monkey.rb file, 196
- folders, 34
 - for files, 219
 - for Ruby program, 12–13
- for loop, 55, 61
- for/in loop, 55

G

- Gedit (Linux), 12
- gems, 287, 299
 - downloading, 220
 - open-uri, 287–289
- gets method, 44
- GitHub, 298, 300
- global variables, 143, 147–148, 170
 - \$home, 169
- greater than (>), 40
- greater than or equal to (>=), 40

- Greetings module, 228
- Grimm, Avdi, 307
- guard_dog.rb file, 193–194

H

- hash, 74–78, 87, 302
 - adding key and value to, 105
 - adding key to, 92
 - automatically running through, 102
 - creating, 76
 - empty? method for, 77
 - within hash, 104–105, 108
 - length method for, 77
 - methods, 88
 - storing in variable, 75
- hash rockets (=>), 76
 - for IRB response, 15
 - for symbol, 96
- hashery_menu.rb file, 80
- hashes, and symbols, 97–101
- has_key? method, 77, 88
- has_value? method, 77, 88
- http://localhost, 297

I

- ID number, 95
- if statement, 38, 45, 238
 - alternatives, 241, 259–260
 - nil in, 120–121
- imagination, 1–2
- implicit return, 261
- include? method, 59
- include statement, 213, 227, 303
- indentation of code, 39
- infinite loop, 50, 61
- information hiding, 309
- inheritance, 185–188, 203–204, 303
 - and mixins, 215–217
 - by SuperSecretAccount class, 201

- initialize method, 154,
 - 182, 194
 - new method and, 141
 - inline code, 238–239
 - input, removing spaces and
 - blank line from, 44
 - input and output (I/O), 263,
 - 265–268
 - insert method, 71, 85
 - inserting variable value into
 - string, 35
 - installing Ruby, 4–7
 - on Mac or Linux, 5–6,
 - 313–314
 - on Windows, 6
 - instance of class
 - creating, 67, 183–184
 - instance variables for, 151
 - instance variables, 143,
 - 150–152, 170
 - and methods, 157–164
 - methods for reading and
 - writing, 160–162
 - methods to see or
 - change, 173
 - instantiating object, 167–168
 - Internet, 9
 - connecting to, 287
 - downloading gems, 220
 - and Ruby, 285–287
 - interrupt signal, 291
 - introduce method, 142
 - invoking methods, 115
 - I/O (input and output), 263,
 - 265–268
 - IOError, 271
 - IRB program, 10–11
 - clearing the screen in, 318
 - finishing your thought
 - in, 318
 - loading script into, 141
 - running scripts in, 45
 - vs. text editor, 14–15
 - is equal to (==), 41
 - is not equal to (!=), 41
 - is-a relationship, 188
 - iterators, 54–55, 302
 - for arrays, 72–74, 87
 - for hash, 88–89
 - in loop, 61
- J**
- join method, 126
- K**
- keys method, 83, 88
 - for hash, 76
 - key-value pairs, 75, 87
- L**
- lambdas, 308–309
 - last method, 85
 - for arrays, 68, 71
 - for range, 89
 - length method, 21, 69,
 - 85, 88
 - for hash, 77
 - less than (<), 40
 - less than or equal to
 - (<=), 40
 - license agreement,
 - accepting, 7
 - Linux
 - changing folders, 13
 - installing Ruby on,
 - 5–6, 314
 - terminal to open
 - IRB, 10
 - text editors for, 12
 - lists. *See* arrays
 - literal string of
 - characters, 29
 - literal syntax, for hash,
 - 76, 87
 - load command, 34, 141
 - loading_docks.rb* file,
 - 277–278
 - local variables, 143,
 - 152–154, 170
 - logical operators, 40–42
 - login account, 199
- loops**, 302
 - for, 55, 61
 - infinite, 50, 61
 - iterators in, 61
 - while, 50–54, 59
- loop_the_loop.rb* file, 58–59
- M**
- Mac
 - changing folders, 13
 - installing Ruby on, 5–6,
 - 313–314
 - terminal to open IRB, 10
 - text editors for, 12
- make_sounds method, 186
- Matsumoto, Yukihiro, 9
- maze.rb* file, 43
- memory, for symbols vs.
 - strings, 94
- menus, 81–84
- Message class, 228
 - vs. instance of Message, 228
- metaprogramming, 309
- methods, 29
 - with ? (question
 - mark), 260
 - adding to class, 141,
 - 156–157
 - arguments for, 117–120
 - blocks for, 132
 - calling, 23–24
 - combining, vs. size
 - management,
 - 251–254
 - defining, 114–120
 - defining local variable
 - outside, 152–153
 - defining variable
 - within, 144
 - for file I/O, 268
 - and instance variables,
 - 157–164
 - invoking, 115
 - modifying, 192
 - modules as
 - collections, 211

- overriding, 190–192, 195, 204–205
- scope for local
 - variables, 146
- simplifying, 244–249
- writing, 130
- Microsoft Word, 12
- MiniTest, 309–310
- minstrel.rb* file, 140–142
- minstrel_review.rb* file, 173
- minstrel_review_2.rb* file, 173–174
- minstrel_review_3.rb* file, 175
- mixins
 - and inheritance, 215–217
 - modules as, 227
- modules, 227, 303
 - creating, 211–212
 - in different files, 230
 - scope, 222
- Monkey class, 183
- monkey.rb* file, 154
- monkey_2.rb* file, 156
- monkey_review_3.rb* file, 172
- mount_proc method, 297
- moving to next array
 - item, 55
- multiplication (*), 25, 28

N

- name method, 158–159
- :name symbol, 174
- NameError error, 146, 171, 221, 317
- names, 248–249, 263
 - arrays for storing, 278
 - for classes, 141
 - of instances, getting and changing, 190
 - method to change, 159–160
 - for methods, 159
 - for scripts, 14
 - and spaces, 23, 30
 - symbols as, 94
 - for variables, 22

- namespaces, modules as, 227
- namespacing, 221, 303
- new method, 138
 - for arrays, 67, 85
 - for class method, 149
 - for hash, 76, 87
 - modules and, 212
- newline (\n), 268, 272
- next method, 25, 29, 55, 61
- nil, 11, 117, 120–122, 125, 237, 262
- nil? method, 242
- no such file or directory
 - error, 316
- NoMethodError error, 155, 159, 162, 212, 228
- NoMethodError: undefined
 - method error, 24
- not (!), 39, 41, 45
- Notepad++, 12
- numbers, 22

O

- object ID, 103, 137–138, 167
- object_id method, 95, 107
- object-oriented program-
ming, 162, 174–176
- objects, 133–137
 - and classes, 137–140, 153, 167–170
 - definition, 142
 - followed by dot and command, 24
 - instantiating, 167–168
 - and self, 154–157
- odd? method, 252
- open method, 280
- opening
 - files, 268–270
 - websites, 288
- open-uri Ruby gem, 287–289, 299
- operators, 24–26
- optional parameters, 119, 130
- or (||), 41, 45
- output, 263, 265–268

- overriding methods, 190–192, 204–205, 303
- overwriting existing
 - files, 271

P

- panda_food.rb* file, 217, 225–226
- parameters, 114
 - vs. arguments, 118
 - optional or default, 119, 130
 - splat, 122–124, 131
- parent class, 188, 204. *See also* superclass
- parentheses [], 119
 - for methods, 115
- pipe character (|), in
 - block, 78
- pirates_and_people.rb* file, 190
- placeholder value, for
 - parameters, 119
- podcasts, on Ruby, 306
- pop method, 72, 85
- pred method, 25, 29
- print command, 43, 44, 59
- printing to screen, puts
 - for, 116
- private methods, 309
- Proc class, 142
- processes, 310
- procs, 308–309
- prompts, 15–16
 - by IRB, 11
- protected methods, 309
- push method, 71, 72, 85
 - shortcut for, 84
- puts self command, 172
- puts statement, 4, 10, 11, 28, 193, 272, 282
 - vs. return, 115–117
- pwd method, 290
- Python, 293–294
 - converting Ruby to, 294, 298

- Q**
- question mark (?)
 - and colon, as `if/else` alternative, 241
 - methods with, 260
- quotation marks (""), 11, 26
 - for strings, 22
- R**
- 'r' mode, 280–281
- Railscasts, 306
- `rand` method, 194, 197
- random number, 194
- `:random_special` key, 84
- ranges, 79, 89
- `read` method, 280
- `readline` method, 282
- `readlines` method, 274, 282
- `refactored.rb` file, 256–257
- refactoring, 233–237, 255–258
- reflection, 27, 309
- regular expressions, 308
- relationship, `is-a`, 188
- `require` method, 218, 287
- `require!` method, 230
- `return` keyword, 117, 123, 244
 - vs. `puts`, 115–117
- `return` value, 117, 131
- `reverse` method, 21, 23–24
- `rewind` method, 272, 274, 282
- RSpec, 310
- Rubular, 308
- `ruby` command, 14–15
- Ruby documentation, 132, 279
- 'ruby' is not recognized ...
 - error message, 6
- Ruby Koans, 307
- Ruby Monk, 308
- Ruby on Rails, 306, 310
- Ruby programming
 - language, 2
 - converting to Python, 294, 298
 - displaying version
 - in Mac or Linux, 5–6
 - in Windows, 6, 7
 - history, 9
 - installing, 4–7
 - on Linux, 314
 - on Mac, 313–314
 - interactive use, 8
 - and Internet, 285–287
 - reasons for learning, 3–4
 - resources, 304–306
- Ruby Rogues, 306
- Ruby Tapas, 307
- Ruby Weekly, 307
- Ruby5 podcast, 306
- RubyGems website, 298, 300
- RubyInstaller (Windows), 7
- Ruby-to-Python project, 298
- running scripts, 13, 33–35
- RVM (Ruby Version Manager), 313, 314
- S**
- `sample` method, 84, 211
- saving scripts, 12–13
- scope, 143, 144–154, 170–174
 - modules, 222
 - top-level, 152–153
- scope resolution operator (`::`), 221, 231
- screen, `puts` for printing to, 116
- scripts, 10, 11, 140, 302
 - creating, 12–13
 - name for, 14
 - running, 13, 45
 - writing and running, 33–35
- `secrecy.rb` file, 200–201
- security, built-in methods for, 203
- `self`, 172, 303
 - displaying value, 172
 - and objects, 154–157
- `self.def` method, 223
- `self.number_of_monkeys` method, 172
- semicolon (;), to end line of code, 212
- `server.rb` file, 290
- `shift` method, 70, 85
- `shovel` operator (`<<`), 84
- shutdown, of web server, 291
- Sinatra (program), 310
- `size` method, 85, 134
- spaces
 - and names, 23, 30
 - removing from input, 44
- splat parameters, 122–124, 131
 - and blocks, 125
- square brackets (`[]`)
 - for arrays, 54, 85, 86
 - for hash values, 87
- stories
 - Apprentice Plumber's Dilemma, 31–33
 - Big Hank's Hashery, 63–66
 - Conclusion, 290
 - Into the Dagron's Lair, 127–129
 - Dial-a-Ballad, or the Minstrel's Delivery Service, 164–166, 177–182
 - File Input and Output, 265–268
 - His Majesty's Flow Control, 35–40
 - King and His String, 19–22, 25–26
 - Method to the Madness, 109–114
 - Queen's Machine, 199–203
 - Refactoring at the Refractory, 233–237
 - Rollicking Ranges, 78–81
 - Ruby on Monorails, 47–50
 - Subject as Object, 133–137
 - Utter Panda-monium, 207–210

- storing hash, in
 - variables, 75
- string interpolation, 35, 45
- strings, 22, 29
 - `#{} for inserting variable value into`, 35, 45
 - backward, 27
 - changing to symbol, 98
 - memory for, 94
 - multiplying, 28
 - quotation marks ("`"`)
 - for, 22
 - vs. symbols, 107
- strings_to_symbols.rb* file, 102–104
- subclass, 188–193, 204
- Sublime Text 2, 12
- subtraction, 25
- super keyword, 192, 196, 204, 205
- superclass, 188–193, 204, 229–230
 - sending right arguments to method, 206
- SuperSecretAccount class, inheritance by, 201
- symbols, 76, 91–97
 - additional features, 104–105
 - basics, 94–97
 - changing strings to, 98
 - and hashes, 97–101
 - memory for, 94
 - vs. strings, 107
- syntax, 4
- SyntaxError error, 96, 317

T

- temporary variable, for array
 - item, 56
- Terminal application, 5
- ternary operator, 241, 253, 260
- text editor, 11–13
 - vs. IRB program, 14–15
- TextEdit (Mac), 12
- threads, 310

- times method, 145
- `to_a` method, 79–80, 83, 89
- top-level scope, 152–153
- `to_s` method, 105, 107
- `to_sym` method, 98, 103, 107
 - for strings, 105
- troubleshooting, 315–319
- true, 32, 45
- truthy values, 245–246, 247, 262–263
- TypeError error, 317–318

U

- undefined local variable or method error, 317
- underscore (`_`), 23
 - in symbol names, 94
- unless statement, 42, 45, 121–122, 238
 - alternatives, 259–260
 - else with, 239
- unshift method, 71, 85
- until, for while loop, 53
- up arrow key, to go
 - back to previous command, 319
- update_tally method, 253

V

- values method, 77, 88
- variables, 22–24, 29, 169
 - assignment tricks, 237–239
 - class, 143, 148–149, 165
 - conditional assignment of
 - value to, 238
 - default value for, 237
 - errors, 145–147
 - global, 147–148
 - inserting values into
 - string, 45
 - instance, 143, 150–152, 172
 - and methods, 157–164
 - methods for reading and writing, 160–162
 - methods to see or change, 173

- local, 143, 152–154
- names for, 22
- scope, 144–154, 170–174
- storing hashes in, 75
- storing symbols in, 105
- storing values in, 117
- temporary, 55
 - two different for same string value, 95
- versions of Ruby
 - displaying in Mac or Linux, 5–6
 - displaying in Windows, 6, 7
- vertical pipe (`|`), in `do/end`, 57
- videos, on Ruby, 307

W

- 'w' (write) mode, 271
- 'w+' (write and read) mode, 279, 281
- web server, 290–296, 299
 - shutdown, 291
- WEBrick, 299, 310
 - shutdown, 297
- web_server.rb* file, 296–297
- websites
 - built-in, 297
 - creating, 310
 - opening, 288
- weezard.rb* file, 148
- weezard_2.rb* file, 150
- when statement, 243
- while loop, 50–54, 59, 61
 - end for, 52
- Windows
 - changing folder, 13
 - installing Ruby on, 6
 - text editors for, 12
- Word (Microsoft), 12
- word processor, 12

Y

- yield keyword, 124, 132

Z

- zero, and arrays, 71